


DECLARATION OF COMPLIANCE

Profile® UP Filter Cartridges

AB Style “W” Code

Cartridge Part Number



This is a guide to the part numbering structure only. For specific options, please contact Pall.

Table 1 : Nominal Length

Code	Description
1	25.4 mm (10")
2	508 mm (20")
3	762 mm (30")
4	1016 mm (40")

Table 2 : Removal Rating

Code	Description
UY020	2 µm
UY045	4.5 µm
UY100	10 µm
UY200	20 µm
UY400	40 µm

Table 3 : Adaptor

Code	Description
3	SOE – single open end with flat closed end and external 222 O-rings
7	SOE – single open end with fin end, 2 locking tabs and external 226 O-rings
8	SOE – single open end with fin end and external 222 O-rings

Table 4 : O-ring Seal Material

Code	Description
H4	Silicone Elastomer
J	Ethylene Propylene Rubber

Profile UP is a 2.5” diameter pleated filter cartridge intended for the filtration of aqueous food and beverage products and beverages with low alcohol concentrations.

An initial flush is recommended prior to use.

Issued 1 May 2009
 Revised 28 February 2017
 Expires 28 February 2019
 Reference FBDCPROFUPENh
 Page 1 of 3



James LeRoy
 Director of Quality
 Pall Cortland

Profile UP Filter Cartridges (AB Style “W” Code)

Components

Filter Media	Pall proprietary melt blown media
Support / Drainage	Extruded polypropylene netting
Helical Wrap	Polypropylene non-woven fabric
Cage, Core, End Cap and Fin End	Polypropylene
Adaptor	Polypropylene with a stainless steel reinforcing ring as appropriate to design
O-ring Seal	Ethylene Propylene Rubber (J) or Silicone Elastomer (H4)

Declaration

Profile UP AB style “W” Code filter cartridges comprise materials that meet regulatory and legislative requirements and guidelines for food contact in that:

Europe

The “W” Code AB style Profile UP filter cartridges meet the requirements for food contact as detailed in European Regulation (EC) Number 1935/2004 in that:

- The materials used to produce “W” Code AB style Profile UP products meet the requirements of Annex I of European Commission Regulation (EU) Number 10/2011, and its amendments, on plastic materials and articles intended to come into contact with foodstuffs (excluding seals).

Migration testing of the filters and components of the Profile UP filters has been performed, and met migration criteria after flushing and in flow conditions, in:

Simulant A (10% ethanol) at 50 °C (122 °F)

Simulant B (3% acetic acid) at 50 °C (122 °F)

Distilled water at 50 °C (122 °F)

Note: This product contains materials that are subject to Specific Migration Limit (SML) requirements. This product contains calcium stearate, which is approved as a direct food additive.

USA

The materials of construction meet the FDA requirements for food contact use as detailed in Code of Federal Regulations, 21 CFR paragraphs 170-199 in that:

- Polypropylene to 21 CFR section 177.1520 (Olefin polymers) and section 178.2010 (antioxidants and/or stabilizers for polymers)
- Ethylene Propylene Rubber and Silicone Elastomeric seal materials to 21 CFR section 177.2600 (Rubber articles intended for repeated use) and conform to 3-A sanitary standard 18-03 Class I for use with milk/butter oil products.

Process Quality System

Site of Manufacture: Pall Cortland, USA

The Quality Management System at Pall Cortland is certified to ISO 9001:2008.

These products / product packaging carry a lot number / date code to facilitate traceability to suppliers' materials and Pall production records.

Supplied in Europe by

Pall International Sàrl
Av. de Tivoli 3
Fribourg
Switzerland
CH-1700


**Pall Food and Beverage**

New York - USA
+1 516 484 3600 telephone
+1 866 905 7255 toll free
foodandbeverage@pall.com

Visit us on the web at www.pall.com

Pall Corporation has offices throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of developments related to products, systems and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 2017, Pall Corporation. Pall,  and Profile are trademarks of Pall Corporation. © indicates a trademark registered in the USA. Filtration.Separation.Solution is a service mark of Pall Corporation.