



# STATEMENT OF COMPLIANCE: ISO 12500-3:2009 Emflon® PFW Filter Cartridges AB Style “W” Code

## Cartridge Part Number



This is a guide to the part numbering structure only. For specific options, please contact Pall.

**Table 1 : Adaptor**

Code	Description
2*	SOE – single open end with flat closed end, 2 locking tabs and external 226 O-rings
7	SOE – single open end with fin end, 2 locking tabs and external 226 O-rings

\*AB05 cartridges only

**Table 2 : Nominal Length**

Code	Description
05*	127 mm (5")
1	254 mm (10")
2	508 mm (20")
3	762 mm (30")

\*Available in Code 2 only

**Table 3 : Seal Material**

Code	Description
H4	Silicone elastomer
J	Ethylene propylene rubber

**Table 4: Elements per Box**

Code	Description
12	Multi-pack of 12 elements in 30" size

For other box quantities please contact Pall

Emflon PFW final air filters are designed for gas filtration in the food and beverage industry, fermenter inlet air and exhaust venting, sterile process air and sterile venting of tanks in food processing.

'Sterile air' is defined as that filtered using a 0.2 µm liquid rated filter (capable of removing 10<sup>7</sup> of *Brevundimonas diminuta* per cm<sup>2</sup> of effective filtration area, in laboratory tests). Please note this product is not supplied pre-sterilized.

The key feature of this product is the inclusion of two layers of Pall proprietary, 0.2 µm microbial rated Emflon PTFE medium in a polypropylene hardware filter construction.

Issued            6 March 2013  
 Revised        11 April 2017  
 Expires        28 February 2019  
 Page            1 of 2

Steven Bailey  
 Quality Manager  
 Pall Manufacturing (UK) Ltd.  
 Ilfracombe, UK

## Emflon PFW Filter Cartridges (“W” Code)

### Components

Filter Media	Two layers of Emflon hydrophobic PTFE media
Support / Drainage	Polypropylene
Side Seal	Polypropylene
Cage, Core, End Cap and Fin End	Polypropylene
Adaptor	Polypropylene (with internal stainless steel reinforcing ring as appropriate to design*)
O-ring Seal	Silicone Elastomer (H4) Ethylene Propylene Rubber (J)

\*For applications requiring autoclaving or steam sterilization, Pall recommends the use of Code 2 or Code 7 adaptors to ensure filter sealing after cooling. Cartridges should be cooled to system operating temperature prior to use.

### Declaration

Emflon PFW filters meet the requirements of ISO12500-3:2009 in that:

Emflon PFW filter cartridges (tested as part number: AB1PFR7WH4) have demonstrated applicable performance capability in laboratory tests as described in report LrF 03b/12 appended. These studies were conducted on randomly sampled product made with the same Pall proprietary hydrophobic PTFE filter membrane, polypropylene support /drainage material and polypropylene hardware; and using the same manufacturing techniques.

### Supplied in Europe by

Pall International Sàrl  
Av. de Tivoli 3  
Fribourg  
Switzerland  
CH-1700



Pall Corporation


#### Pall Food and Beverage

New York - USA  
+1 516 484 3600 telephone  
+1 866 905 7255 toll free  
foodandbeverage@pall.com

Visit us on the web at [www.pall.com](http://www.pall.com)

Pall Corporation has offices throughout the world. For Pall representatives in your area, please go to [www.pall.com/contact](http://www.pall.com/contact).

Because of developments related to products, systems and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit [www.pall.com](http://www.pall.com) to verify that this information remains valid.

© Copyright 2017, Pall Corporation. Pall,  and Emflon are trademarks of Pall Corporation. © indicates a trademark registered in the USA. Filtration.Separation.Solution is a service mark of Pall Corporation.

April 2017